

[54] **METHOD OF MAKING A HINGED DISPLAY MOUNT**

[76] Inventor: **Carroll N. Cross**, 3202 Holiday Ave.,
Apopka, Fla. 32703

[21] Appl. No.: **355,985**

[22] Filed: **May 22, 1989**

[51] Int. Cl.⁵ **B32B 31/18**

[52] U.S. Cl. **156/223; 156/227;**
156/256; 156/264; 156/265; 40/119; 40/120;
40/124.1; 40/124.4; 248/463; 281/30; 16/225

[58] Field of Search 156/264, 265, 227, 223,
156/256; 40/119, 120, 124.1, 124.4; 248/463;
281/30; 16/225, 385

[56] **References Cited**

U.S. PATENT DOCUMENTS

1,845,952	2/1932	Wright	281/30
1,907,261	5/1933	Shedd	40/119
2,568,458	9/1951	Nichols	156/253
2,784,929	3/1957	Diening	248/463
3,002,720	10/1961	Cross	248/463

3,188,113	6/1965	Cross	281/30
3,198,339	8/1965	Stolarz	40/120
3,281,975	11/1966	Simone	40/120
3,713,578	1/1973	Johnson	16/225
4,299,643	11/1981	Cross	156/223

Primary Examiner—Caleb Weston

Attorney, Agent, or Firm—William M. Hobby, III

[57] **ABSTRACT**

A process of making a casebound hinged display mount having three rectangular panels and a pen holding slot formed in one edge of one of the rectangular panels for supporting the pen once the display mount has been set up. The process includes having a thin aluminum strip hinge with a visible groove in the case binding and aluminum strip hinge to make it easier to set up the display mount. The visible hinge line also allows the display mount to be shipped with a pen positioned in the visible groove and placed in the pen holding slot when the display mount is set up.

8 Claims, 2 Drawing Sheets

